DEBS INTERNATIONAL FACTORY

For MasterBatch & Compound C.R: 4030238393

Kingdom of Saudi Arabia – Jeddah



مصنع دبس العالميه

لصناعة الاصبغة و الحبيبات البلاستيكيه س.ت : 4030238393 المملكه العربية السعوديه –جده

Product Data Sheet Product: PPA Additive Master Batch Grade-AE-12024

Product description

Debs PPA additive specially designed for blown film applications. Debs PPA use to eliminate melt fraction, reduce extruder pressure, improve surface finish and reduce die build up during extrusion of Polyolefin films

Typical recommendation

Recommended dosage level range 2-4% or as required to get desire level. Applications: Polyolefin films.

Typical value

S.No.	Properties	Unit	Specification
1	Carrier Resin		Polyethylene
2	Moisture content	%	<0.1
3	Bulk density	gm/litre	550-650
4	Melt Flow Index	g/10Min.	5±2
	@190DC/2.16kgs		

Storage condition: Material should be stored in cool and dry place and well ventilated area, away from incompatible materials. Proper storage will allow to store this grade up to 02years from date of manufacturing.

This PPA additive master batch tested in our lab at our standard testing condition and results may vary under different condition depending upon the accuracy of man and machines.

Debs International Factory does not give any liability of the abnormality occurs during processing. This is the sole responsibility of user and this is recommended to test the material for suitability of the grade.

Issued Date:02/10/2023